LKPv 8420

MediLine

Linemas S2	بم	

Gross/net capacity	856/– litre	
Ext. dimensions in mm (w/d/h)	790/980/2160	
Int. dimensions in mm (w/d/h)	620/850/1550	
Energy consumption in 365 days	603 kWh	
Climate rating	5 ¹	
Refrigerant	R 290	
Airborne acoustical noise emissions	58 dB(A)	
Connection Rating	2.0 A	
Voltage	220-240 V~	
Cooling system	forced-air	
Defrosting	automatic	
Temperature range	-2°C to +16°C	
Gradient *	2.1°C	
Max. fluctuation **	1.8°C	
Housing material/colour	steel/white	
Door/lid material	Steel	
Liner Material	304-grade stainless steel	
Type of Control	electronic controller	
Temperature display	außen digital	
Fault: warning signal	visual and audible	
Interface	RS 485	
volt-free alarm contact	yes	
Adjustable Shelving	4	
Shelf material	grid shelves plastic-coated	
Shelf loading	60 kg	
Castors/type of castors	yes/swivel castors	
Handle	full-length integrated door handle	
Lock	fitted	
Self-closing door	yes	
Door hinges	right, reversible	
Insulation	83-60 mm	
Gross/net weight	178 / 147 kg	
EAN-Nr.	9005382196793	

1 Climate class / Climate $R\overline{a}$ ting: SN +10°C to +32°C

3 +10°C to +25°C

N +16°C to +32°C **4** +10°C to +30°C **ST** +16°C to +38°C 5 +10°C to +40°C

T +16°C to +43°C **7** +10°C to +35°C

^{*} Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.