

# Magnetic stirrer

analog, up to 1,500 rpm, ceramic-coated plate 180x180 mm

up to 1500  
rpm



## MS-20A analog

### Ideal for:

- mixing of chemical, laboratory and pharmaceutical materials
- heat-sensitive procedures in microbiology and biochemistry

### Features:

- up to 1,500 rpm
- ceramic-coated aluminium plate 180x180 mm
- heat-, chemical- and restricted acid-resistant
- powder-coated aluminium body
- 30 mm stirrer bar included
- CE certified and unique serial number for tracing

### Safety mechanism:

- operation LEDs

### Controller:

- **PWM controller**



Stirrer bar included

<b>Model</b>	<b>MS-20A</b>
<b>Body</b>	powder-coated aluminium
<b>Plate</b>	ceramic-coated aluminium (heat-, chemical- and acid-resistant), 180x180 mm
<b>Stirring capacity</b>	max. 20 l
<b>Speed</b>	up to 1,500 rpm
<b>Controller</b>	superior linearity PWM Controller
<b>Stirring bar</b>	30 mm bar included, usable up to 50 mm bar
<b>Permissible temperature &amp; RH %</b>	ambient temperature +5 ~ 50°C, 85% RH
<b>Dimension &amp; weight</b>	206x307xh99 mm, 3.1 kg
<b>Packaging size</b>	400x280xh200 mm, 5 kg
<b>Power supply</b>	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz
<b>Order number 230V</b>	<b>DH.WMS03122</b>
<b>Order number 120V</b>	<b>DH.WMS02122</b>

Accessories: External temperature probes, stand rod, stirring bars and holder / clamp / clip on page 27 & 28